

# SOLV-UR

thinner  
(TU 2319-032-12288779-2002)



## PRODUCT DESCRIPTION:

SOLV-UR is a mixture of aromatic hydrocarbon and acetate esters.

## RECOMMENDED USE:

- SOLV-UR is applied:
- as thinner for polyurethane paints and ZINOL<sup>®</sup> produced by VMP GROUP;
  - for cleaning equipments;
  - for removing of oil and grease from metal surfaces according to GOST 9.402-2004.

## CERTIFICATES/APPROVALS:

The sanitary-and-epidemiologic certificate №66.01.40.231.П.000069.01.09/20 January.2009; Register of NK RosNeft OJSC

## TECHNICAL DATA:

Appearance	colorless or slightly yellowish clear liquid free from suspended matter
Specific gravity	0.82 g/ml, not less

## STORAGE AND HANDLING:

SOLV-UR is packaged in metal drums and cans by 80, 36 and 17 kg and in plastic cans by 4 kg.

Store in dry, shaded conditions away from sources of heat, moisture and ignition, GOST 9980.5-2009

Guaranteed shelf life in the manufacturer's package units is 24 months from the date of packaging.

## SAFETY PRECAUTIONS

SOLV-UR has the fourth class of hazard, GOST 12.1007-76. It is necessary to follow all local or national safety regulations.



**VMP RESEARCH & PRODUCTION HOLDING JOINT-STOCK COMPANY (VMP HOLDING)**  
105, Amundsen St., **Ekaterinburg**, 620016, Russia, tel./fax.: +7 343 267 94 31; 266 09 15;  
E-mail: [office@fmp.ru](mailto:office@fmp.ru);  
WEB: [www.coldzinc.ru](http://www.coldzinc.ru)  
**Moscow**, tel./fax.: +7(495) 955-12-64; 955-12-63; e-mail: [svx@fmp.ru](mailto:svx@fmp.ru)  
**St. Peterburg**, tel./fax.: +7(812) 449-48-00; e-mail: [spb@fmp.ru](mailto:spb@fmp.ru)  
**Voronezh**, tel.: +7(4732) 20-55-98; e-mail: [zamet@comch.ru](mailto:zamet@comch.ru)  
**Novosibirsk**, tel.: +7(383) 205-07-00; e-mail: [alex@stroy-nsk.ru](mailto:alex@stroy-nsk.ru)